## NSN 5910-00-484-4962



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-484-4962 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.312 inches **Body Length:** 0.874 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 47000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 300.0 ac-rms single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 50000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Terminal Surface Treatment: Case Insulation Material:** 

Plastic

## **Test Data Document:**

96214-530537 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-00-484-4962

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_		ш	ıιa	114	au	VII	١.

No

Fiig:

A010b0