NSN 5910-00-484-5188

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-484-5188

Body Style:
Piston
Overall Length:
0.875 inches
Shaft Diameter:
0.121 inches single shaft
Shaft Length:
0.125 inches single shaft
Body Length:
0.750 inches
Overall Diameter:
0.312 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.703 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.235 inches
Quality Factor At 25 Deg Celsius:
500.0
Inclosure Type:
Encased
Adjustment Device Torque:
Between 1.000 inch-ounces and 8.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
1000.0 gigohms
Mounting Facility Type And Quantity:
2 terminal
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Shaft Type:
Round, slotted single shaft
Capacitance Range In Picofarads:
+1.0/+14.0 single section
Nonderated Voltage Rating And Type:
1000.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Test Data Document:
45413-112492-0006 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 wire lead

Terminal Type And Quantity:

NSN 5910-00-484-5188

Glass Dielectric Variable Capacitor - Page 2 of 2



Shelf Li	ife:
N/a	
IIInit Of	N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0