NSN 5910-00-484-5189

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-484-5189

Body Style: Piston **Overall Length:** 1.330 inches **Shaft Diameter:** 0.121 inches single shaft **Shaft Length:** 0.125 inches single shaft **Body Length:** 1.205 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.703 inches Center To Center Distance Between Terminals Parallel To Diameter: 0.235 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Inclosure Type: Encased Adjustment Device Torque:** Between 1.000 inch-ounces and 8.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Shaft Type:** Round, slotted single shaft Capacitance Range In Picofarads: +1.0/+42.0 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 shaft **Test Data Document:** 45413-112492-007 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 wire lead

Terminal Type And Quantity:

NSN 5910-00-484-5189

Glass Dielectric Variable Capacitor - Page 2 of 2



SI	nel	lf I	l if	ρ.
Ο.		•		v.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0