

View Online at https://aerobasegroup.com/nsn/5910-00-484-5189

Во	dy Style:
Pis	ston
Ov	erall Length:
1.3	30 inches
Sh	aft Diameter:
0.1	21 inches single shaft
Sh	aft Length:
0.1	25 inches single shaft
Во	dy Length:
1.2	205 inches
Ov	erall Diameter:
0.3	12 inches
Ter	mpurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-50	0.0/+50.0 single section
Ce	nter To Center Distance Between Terminals Parallel To Length:
0.7	703 inches
Ce	nter To Center Distance Between Terminals Parallel To Diameter:
0.2	35 inches
Qu	ality Factor At 25 Deg Celsius:
500	0.0
Inc	slosure Type:
End	cased
Ad	justment Device Torque:
Bet	tween 1.000 inch-ounces and 8.000 inch-ounces
Ins	sulation Dc Resistance At 25 Deg Celsius:
100	00.0 gigohms
Мо	ounting Facility Type And Quantity:
2 te	erminal
No	nderated Operating Temp:
Bet	tween -55.0 degrees celsius and 125.0 degrees celsius
Sh	aft Type:
Ro	und, slotted single shaft
Ca	pacitance Range In Picofarads:
+1.	.0/+42.0 single section
No	nderated Voltage Rating And Type:
100	00.0 dc continuous single section
Ad	justment Device Drive Type And Quantity:
1 s	haft
	st Data Document:
	413-112492-007 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
	.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
_	rminal Type And Quantity:

2 wire lead



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0