

View Online at https://aerobasegroup.com/nsn/5910-00-485-4721

### **Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.344 inches

#### **Body Length:**

0.125 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.220 inches and 0.280 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

36.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

10000.0 megohms

# **Quality Factor At Reference Temp:**

1000.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# NSN 5910-00-485-4721

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

