NSN 5910-00-486-7279

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-486-7279

Body Style: W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.335 inches **Body Width:** 0.330 inches **Body Height:** 0.145 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.119 inches and 0.181 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 5000.0 megohms **Capacitance Value Per Section:** 27.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section **Tolerance Range Per Section:** -2.00 to 2.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0030

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-5+18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-00-486-7279

Mica Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0