Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-488-4721

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Body Diameter:

1.437 inches

Body Length:

4.500 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

33.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

270.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

14.0000

Dc Leakage At Reference Temp:

427.000 microamperes

Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-62+12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

NSN 5910-00-488-4721

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0