NSN 5910-00-489-1353

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-489-1353 |
|---|
| Body Style: |
| Rotary |
| Overall Height: |
| 0.310 inches |
| Overall Diameter: |
| 0.375 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| -1500.0 single section |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.300 inches |
| Quality Factor At 25 Deg Celsius: |
| 500.0 |
| Inclosure Type: |
| Encased |
| Adjustment Device Torque: |
| Between 1.000 inch-ounces and 6.000 inch-ounces |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 10.0 gigohms |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +15.0 to 60.0 single section |
| Nonderated Voltage Rating And Type: |
| 200.0 dc continuous single section |
| Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: |
| +6.00 to 16.00 and -15.00/-9.00 single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Capacitance Drift In Picofarads: |
| 0.50 single section |
| Terminal Type And Quantity: |
| 2 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |