NSN 5910-00-490-8273

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-490-8273

Body Style: W/o mtg facilities, axial terminals Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:	
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	• •
Not established Terminal Length: 1.500 inches Body Diameter: 0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	W/o mtg facilities, axial terminals
Terminal Length: 1.500 inches Body Diameter: 0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Reliability Indicator:
1.500 inches Body Diameter: 0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Not established
Body Diameter: 0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Terminal Length:
0.770 inches Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	1.500 inches
Body Length: 1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Body Diameter:
1.593 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	0.770 inches
Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Body Length:
O.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	1.593 inches
Schematic Diagram Designator: No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Terminal Diameter:
No common or grounded electrode (s) Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	0.032 inches
Features Provided: Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Schematic Diagram Designator:
Hermetically sealed case Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	No common or grounded electrode (s)
Capacitance Value Per Section: 3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Features Provided:
3.000 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Hermetically sealed case
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Capacitance Value Per Section:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	3.000 microfarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Nonderated Operating Temp:
Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Between -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Nonderated Continuous Voltage Rating And Type Per Section:
-5.00/+5.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	200.0 dc single section
Case Material: Metal Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Tolerance Range Per Section:
Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	-5.00/+5.00 percent single section
Insulation Resistance At Reference Temp: 100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Case Material:
100000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Metal
Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Insulation Resistance At Reference Temp:
0.5000 Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	100000.0 megohm-microfarads
Terminal Surface Treatment: Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Dissipation Factor At Reference Tempurature In Percent:
Solder Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	0.5000
Case Insulation Material: Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Terminal Surface Treatment:
Plastic Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Solder
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Case Insulation Material:
2 uninsulated wire lead Shelf Life: N/a	Plastic
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 uninsulated wire lead
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	

No

Demilitarization:

NSN 5910-00-490-8273

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0