

View Online at <https://aerobasegroup.com/nsn/5910-00-491-6437>

Body Style:

Rotary

Terminal Length:

0.137 inches

Overall Height:

0.177 inches

Overall Diameter:

0.216 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-33.0 single section

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-50.0 to 70.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.196 inches

Terminal Diameter:

0.043 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.196 inches

End Application:

Landing craft air cushio (lca), virginia class cgn(41), spruance class dd(963), sturgeon class ssn(637), los angeles class ssn(688), nimitz class cvn, ticonderoga class cg(47), forrestal class cv, engine aircraft tf33-pw-102(c-135e, ec-135h/k/p)

Inclosure Type:

Encapsulated

Terminal Location:

Opposite sides on end opposite adjustment control bent forward

Adjustment Device Torque:

Between 0.700 inch-ounces and 2.100 inch-ounces

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Criticality Code Justification:

Feat

Capacitance Range In Picofarads:

+2.5 to 5.0 single section

Nonderated Voltage Rating And Type:

63.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 rotor w/screwdriver slot

Special Features:

Weapons system essential

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0