Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-491-6500

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.609 inches

Terminal Length:

0.125 inches

Bushing Diameter:

0.190 inches

Bushing Length:

0.203 inches

Body Length:

0.281 inches

Overall Diameter:

0.220 inches

Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:

50.0 single section

Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Quality Factor At 25 Deg Celsius:

5000.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Torque:

Between 0.500 inch-ounces and 4.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

1000.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.190 inches

Air Dielectric Variable Capacitor - Page 2 of 2



Capacitance Range In Picofarads: +0.4/+2.0 single section Nonderated Voltage Rating And Type: 250.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 1 threaded stud Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A096a0