Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-491-9088

### **Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

Terminal Length:

0.750 inches

Body Length:

Between 1.750 inches and 1.876 inches

#### **Body Width:**

Between 0.625 inches and 0.751 inches

#### **Body Height:**

Between 2.812 inches and 2.938 inches

### Schematic Diagram Designator:

Delta connected

#### Section Quantity:

3

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

## Capacitance Value Per Section:

1.020 microfarads all sections

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

90.0 ac-rms all sections

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent all sections

#### **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

## Dissipation Factor At Reference Tempurature In Percent:

1.000

# **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

--

Paper Dielectric Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

