## NSN 5910-00-492-2906

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5910-00-492-2906

View Online at https://aerobasegroup.com/nsn/5910-00-492-2906
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.120 inches
Body Length:
0.800 inches
Body Width:
0.250 inches
Body Height:
0.800 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
15000.0 megohms
Capacitance Value Per Section:
2000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:
-20.0 to 100.0 single section
Tolerance Range Per Section:
-5.00 to 5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.0013
Test Data Document:
81349-mil-c-5/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5910-00-492-2906

Mica Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0