

View Online at <https://aerobasegroup.com/nsn/5910-00-493-0684>

Body Style:

Rotary

Body Diameter:

0.218 inches

Body Height:

0.280 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.195 inches

Quality Factor At 25 Deg Celsius:

500.0

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 0.500 inch-ounces and 3.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+2.0 to 5.0 single section

Nonderated Voltage Rating And Type:

100.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50 to 2.00 and -4.20 to 3.40 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Test Data Document:

13499-917-1260-080 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0