

View Online at <https://aerobasegroup.com/nsn/5910-00-493-4845>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 0.406 inches and 0.468 inches

Body Diameter:

Between 1.360 inches and 1.390 inches

Body Length:

Between 3.438 inches and 3.562 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.422 inches and 0.452 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.833 inches and 0.853 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Electrical Polarization:

Nonpolarized

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting holes

Capacitance Value Per Section:

160.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

1.33

Dc Leakage At Reference Temp:

1.000 milliamperes

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0