

View Online at https://aerobasegroup.com/nsn/5910-00-493-5780

# **Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:** 

Not established

# Width Across Flats:

0.187 inches

**Body Length:** 

0.359 inches

## Schematic Diagram Designator:

Feedthrough

## Mounting Facility Screw Thread Series Designator:

#### Unc

## Mounting Facility Type And Quantity:

1 threaded bushing

**Features Provided:** 

Mounting hardware

## **Capacitance Value Per Section:**

500.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-56.0/+22.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## **Thread Size:**

0.164 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+80.00 percent single section

## **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

10000.0 megohms

# Power Factor At Reference Tempurature In Percent:

3.5000

## **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0