

View Online at <https://aerobasegroup.com/nsn/5910-00-494-4662>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Body Diameter:

1.312 inches

Body Length:

2.562 inches

Schematic Diagram Designator:

One terminal common to each section

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

244.0

Electrical Polarization:

Polarized

Section Quantity:

3

Capacitance Value Per Section:

36.000 microfarads 2nd section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

150.0 dc 3rd section

Tolerance Range Per Section:

-10.00/+75.00 percent 3rd section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Temperature In Percent:

12.0000

Dc Leakage At Reference Temp:

110.000 microamperes

Terminal Surface Treatment:

Nickel

Case Insulation Material:

Plastic

Test Data Document:

81349-milc62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milc62/10 specification

(includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0