NSN 5910-00-495-7254

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-495-7254 **Body Style:** W/o mtg facilities, axial terminals Mil-std-1276 Wire Lead Type Designator: N-2 **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.180 inches **Body Length:** 0.562 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohms **Capacitance Value Per Section:** 16660.000 picofarads single section **Nonderated Operating Temp:** Between -62.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -0.25/+0.25 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.2000 **Terminal Surface Treatment:** Gold **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5910-00-495-7254

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0