Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-495-8469

### **Body Style:**

W/o mtg facilities, terminal (s) on one surface

## **Reliability Indicator:**

Not established

### Body Length:

3.750 inches

### **Body Width:**

2.500 inches

#### **Body Height:**

5.750 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 1.813 inches and 2.062 inches

Terminal Height From Body:

2.750 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

300.0 megohm-microfarads

# Capacitance Value Per Section:

0.500 microfarads single section

### Nonderated Operating Temp:

Between -65.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

10000.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

25000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

### Test Data Document:

81349-milc19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milc19978/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 threaded stud

Shelf Life:

NI/o

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0