Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-497-4129

## **Body Style:**

W/o mtg facilities, axial terminals

# **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.219 inches

#### **Body Length:**

0.578 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

#### Impedance At Minimum Operating Tempurature In Ohms:

. 500.0

# Electrical Polarization:

Polarized

#### **Capacitance Value Per Section:**

4.700 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

2.0 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Tantalum

## Power Factor At Reference Tempurature In Percent:

3.6000

#### Equivalent Series Resistance At Reference Tempurature In Ohms:

10.00

# Dc Leakage At Reference Temp:

1.000 microamperes

# **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

# NSN 5910-00-497-4129

Electrolytic Fixed Capacitor - Page 2 of 2



## **Test Data Document:**

94580-1997201 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A010b0