

View Online at <https://aerobasegroup.com/nsn/5910-00-497-8921>

**Body Style:**

W/o mtg facilities, radial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.500 inches

**Body Diameter:**

0.580 inches

**Body Length:**

0.200 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.375 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Forrestal class cv; oliver perry class ffg; sturgeon class ssn (637); spruance class dd (963); tarawa class lha; ticonderoga class cg (47); arleigh burke class ddg; austin ship class lpd-4 amphibious transport docks; sirius class t-afs 8; nimitz class cvn

**Capacitance Value Per Section:**

50000.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-56.0/+22.0 without voltage applied single section

**Nonderated Operating Temp:**

Between -10.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

250.0 ac-rms 1st section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Terminal Surface Treatment:**

Solder

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0