

View Online at <https://aerobasegroup.com/nsn/5910-00-498-5584>

**Body Style:**

Rotary

**Overall Height:**

0.310 inches

**Overall Diameter:**

0.370 inches

**Dissipation Factor At 25 Deg Celsius In Percent:**

0.2

**Inclosure Type:**

Encapsulated

**Adjustment Device Torque:**

Between 1.000 inch-ounces and 6.000 inch-ounces

**Insulation Dc Resistance At 25 Deg Celsius:**

10.0 gigohms

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Capacitance Range In Picofarads:**

+2.0 to 8.0 single section

**Nonderated Voltage Rating And Type:**

350.0 dc continuous single section

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

-4.50 to 2.00 and -2.50 to 2.00 single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.50 single section

**Test Data Document:**

81349-mil-c-81 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A096a0