Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-498-8215

#### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

### **Terminal Length:**

2.250 inches

#### **Body Diameter:**

0.312 inches

#### **Body Length:**

0.719 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

#### Impedance At Minimum Operating Tempurature In Ohms:

65.0

# Electrical Polarization:

Polarized

### **Features Provided:**

Hermetically sealed case

#### **Capacitance Value Per Section:**

40.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Dc Leakage At Maximum Operating Temp:

5.0 milliamperes

### Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### Case Material:

Metal

### **Capacitive Electrode Material:**

Tantalum

# Power Factor At Reference Tempurature In Percent:

12.1000

### Dc Leakage At Reference Temp:

1.000 microamperes

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2



# Test Data Document:

81349-milc3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-milc3965-24 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A010b0