

View Online at <https://aerobasegroup.com/nsn/5910-00-499-7484>

Body Style:

W/thd mtg studs, axial terminals

Reliability Indicator:

Not established

Terminal Length:

0.296 inches

Body Diameter:

0.400 inches

Body Length:

1.124 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.625 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Internal Electrical Connection Type:

Extended foil

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting studs

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

Capacitance Value Per Section:

68000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0