## NSN 5910-00-499-7757

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-499-7757

**Body Style:** 

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.500 inches

**Body Diameter:** 

Between 0.336 inches and 0.367 inches

**Body Length:** 

0.922 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

150.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

250.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:** 

8.0000

Dc Leakage At Reference Temp:

20.000 milliamperes

**Test Data Document:** 

81349-mil-c-26655/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-499-7757

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0