## NSN 5910-00-501-0984

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-501-0984 **Body Style:** Piston **Bushing Diameter:** 0.193 inches **Bushing Length:** 0.281 inches **Body Length:** 0.469 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -150.0/+150.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/double flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.150 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.190 inches Capacitance Range In Picofarads: +1.0/+14.0 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw

1 Slotted Screw

**Capacitance Drift In Picofarads:** 

0.04 single section

## NSN 5910-00-501-0984

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0