

View Online at <https://aerobasegroup.com/nsn/5910-00-501-1894>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.469 inches

Bushing Diameter:

0.047 inches

Bushing Length:

0.234 inches

Body Length:

0.266 inches

Overall Diameter:

0.281 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

60.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Quality Factor At 25 Deg Celsius:

4000.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Torque:

Between 1.000 inch-ounces and 5.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

Capacitance Range In Picofarads:

+0.8/+10.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.01 single section

Terminal Type And Quantity:

1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0