## NSN 5910-00-501-1894

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-501-1894 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.469 inches **Bushing Diameter:** 0.047 inches **Bushing Length:** 0.234 inches **Body Length:** 0.266 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 60.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 4000.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 1.000 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.234 inches

**Capacitance Range In Picofarads:** 

+0.8/+10.0 single section

## NSN 5910-00-501-1894

Air Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Typ
250.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

**Capacitance Drift In Picofarads:** 

0.01 single section

**Terminal Type And Quantity:** 

1 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0