## NSN 5910-00-504-3915

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-504-3915

#### **Body Style:**

W/o mtg facilities, terminal (s) on one end

#### **Reliability Indicator:**

Not established

## **Terminal Length:**

0.411 inches

#### **Body Diameter:**

1.375 inches

#### **Body Length:**

4.250 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

0.687 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Electrical Polarization:**

Polarized

#### **Capacitance Value Per Section:**

2200.000 microfarads single section

#### Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

15.0000

Dc Leakage At Reference Temp:

410.000 microamperes

#### **Test Data Document:**

81349-milc-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

2 insulated wire lead w/terminal lug

Shelf Life:

N/a

- Unit Of Measure:
- ---
- Demilitarization:
- No

# NSN 5910-00-504-3915

Electrolytic Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

