

View Online at <https://aerobasegroup.com/nsn/5910-00-506-4235>

Body Style:

W/mtg bracket, axial terminals

Reliability Indicator:

Not established

Terminal Length:

0.875 inches

Body Diameter:

2.400 inches

Mounting Slot Width:

Between 0.109 inches and 0.115 inches

Body Length:

4.000 inches

Continuous Current Rating In Amps:

200.0

Terminal Diameter:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

2.500 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Type And Quantity:

3 mounting slots

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

5.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

370.0 ac-rms single section and 1000.0 dc single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100.0 megohms

Dissipation Factor At Reference Temperature In Percent:

1.000

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0