NSN 5910-00-510-6605

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-510-6605 **Body Style:** W/thd mtg hol (s)/stud(s) terminal(s) on one surface **Reliability Indicator:** Not established **Body Length:** 1.406 inches **Body Width:** 1.406 inches **Body Height: 3.438** inches **Schematic Diagram Designator:** No common or grounded electrode (s) Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 2 threaded mounting studs **Capacitance Value Per Section:** 4.280 microfarads single section **Nonderated Operating Temp:** Between -50.0 degrees celsius and 70.0 degrees celsius **Thread Size:** 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section **Tolerance Range Per Section:** -0.00 to 2.00 percent single section **Case Material:** Metal **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate **Test Data Document:** 18876-8516413 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life:

--

N/a

Unit Of Measure:

NSN 5910-00-510-6605

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0