NSN 5910-00-512-1318

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-512-1318

g
Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
1.750 inches
Body Width:
0.875 inches
Body Height:
1.000 inches
Center To Center Distance Between Terminals Parallel To Length:
0.938 inches
Terminal Height From Body:
0.563 inches
Unthreaded Mounting Hole Diameter:
Between 0.203 inches and 0.208 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.625 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.625 inches
Mounting Facility Type And Quantity:
4 unthreaded mounting holes
Capacitance Value Per Section:
4.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
150.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5910-00-512-1318

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0