

View Online at <https://aerobasegroup.com/nsn/5910-00-514-2038>

Body Style:

W/mtg bracket, terminals on opposite ends

Reliability Indicator:

Not established

Terminal Length:

0.750 inches

Body Diameter:

Between 1.000 inches and 1.062 inches

Body Length:

Between 2.782 inches and 2.844 inches

Continuous Current Rating In Amps:

200.0

Terminal Diameter:

0.312 inches

Unthreaded Mounting Hole Diameter:

0.150 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Type And Quantity:

4 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.100 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 150.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dielectric Material:

Paper

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0