

View Online at <https://aerobasegroup.com/nsn/5910-00-516-9566>

**Body Style:**

W/o mtg facilities, axial terminals

**Mil-std-1276 Wire Lead Type Designator:**

N-3

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.1000

**Terminal Length:**

1.500 inches

**Body Diameter:**

0.406 inches

**Body Length:**

2.203 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Impedance At Minimum Operating Temperature In Ohms:**

97.0

**Electrical Polarization:**

Nonpolarized

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

35.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

80.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

75.0 dc single section

**Tolerance Range Per Section:**

-15.00/+50.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

15.0000

**Dc Leakage At Reference Temp:**

5.000 microamperes

**Case Insulation Material:**

Plastic

**Test Data Document:**

81349-mil-c-39006 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-39006/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0