

View Online at <https://aerobasegroup.com/nsn/5910-00-517-9095>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

1.750 inches

Body Width:

0.875 inches

Body Height:

0.750 inches

Center To Center Distance Between Terminals Parallel To Length:

1.000 inches

Terminal Height From Body:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.125 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Helicopter, search and rescue, hh-60h, helicopter, advance attack, ah-1w, helicopter, mh-53e, helicopter, uscg search and rescue, hh-60j, helicopter, carrier based asw, sh-60f, aircraft, tomcat f-14, aircraft, c-2a (reprocured), aircraft, viking s-3b.

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.500 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Power Factor At Reference Temperature In Percent:

1.0000

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0