

View Online at <https://aerobasegroup.com/nsn/5910-00-517-9095>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Body Length:**

1.750 inches

**Body Width:**

0.875 inches

**Body Height:**

0.750 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.000 inches

**Terminal Height From Body:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.125 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Helicopter, search and rescue, hh-60h, helicopter, advance attack, ah-1w, helicopter, mh-53e, helicopter, uscg search and rescue, hh-60j, helicopter, carrier based asw, sh-60f, aircraft, tomcat f-14, aircraft, c-2a (reprocured), aircraft, viking s-3b.

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

0.500 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

600.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Power Factor At Reference Temperature In Percent:**

1.0000

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0