## NSN 5910-00-518-0803

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-518-0803 **Body Style:** Piston **Overall Length:** 0.850 inches **Bushing Diameter:** 0.191 inches **Bushing Length:** 0.250 inches **Body Length:** 0.828 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 800.0 **End Application:** General application electronics (gen-ap-e) **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 8.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 10000000.0 megohms **Bushing Width:** 0.171 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.190 inches

**Capacitance Range In Picofarads:** 

+0.8/+16.0 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:** 

1 slotted screw

## NSN 5910-00-518-0803

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0