## NSN 5910-00-519-4374

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-519-4374

**Body Style:** W/o mtg facilities, radial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.180 inches **Body Length:** 0.375 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.250 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohms **Capacitance Value Per Section:** 39.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -330.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -60.0/+60.0 single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Ceramic **Insulation Resistance At Reference Temp:** 50000.0 megohms **Quality Factor At Reference Temp:** 1000.0000 **Terminal Surface Treatment:** 

## **Test Data Document:**

Solder

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## NSN 5910-00-519-4374

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

81349-mil-c-20/1c government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0