

View Online at <https://aerobasegroup.com/nsn/5910-00-520-3498>

Body Style:

W/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

N-2

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Diameter:

0.100 inches

Body Length:

0.170 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

1000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-30.0/+10.0 without voltage applied single section

Nonrated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonrated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

2.5000

Terminal Surface Treatment:

Gold

Test Data Document:

94756-441-0877 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0