

View Online at https://aerobasegroup.com/nsn/5910-00-520-3499

## **Body Style:**

W/o mtg facilities, axial terminals

## Mil-std-1276 Wire Lead Type Designator:

N-2

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.100 inches

**Body Length:** 

0.170 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

4700.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-30.0/+10.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

## **Terminal Surface Treatment:**

Gold

# Test Data Document:

94756-441-0877 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5910-00-520-3499

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

