

View Online at https://aerobasegroup.com/nsn/5910-00-523-9477

Plastic Dielectric Fixed Capacitor - Page 1 of 2

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.750 inches

Body Length:

Between 1.750 inches and 1.876 inches

Body Width:

Between 0.937 inches and 1.063 inches

Body Height:

Between 0.750 inches and 1.063 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.094 inches and 2.156 inches

Schematic Diagram Designator:

Delta, connected, grounded to case

Internal Electrical Connection Type:

Extended foil

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Section Quantity:

3

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.033 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc all sections

Tolerance Range Per Section:

-5.00/+5.00 percent all sections

Case Material:

Metal

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic and paper

Terminal Type And Quantity:

3 tab, solder lug

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0