NSN 5910-00-525-3885

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-525-3885

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.100 inches
Body Width:
0.100 inches
Body Height:
0.100 inches
Center To Center Distance Between Terminals Parallel To Length:
0.100 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
1.900 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
remparation occurrence of expansions of economic print of Eog economic
0.0 single section
0.0 single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section:
0.0 single sectionNonderated Continuous Voltage Rating And Type Per Section:200.0 dc single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp:
0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000 Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Tolerance Range Per Section: -0.10/+0.10 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000 Terminal Type And Quantity: 2 uninsulated wire lead

-

NSN 5910-00-525-3885

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0