NSN 5910-00-538-1420

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-538-1420 **Body Style:** W/mtg bracket, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.670 inches **Body Length:** 1.812 inches **Body Width:** 0.670 inches **Body Height:** 1.108 inches **Terminal Diameter:** 0.032 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Internal Electrical Connection Type:** Inserted tab **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -20.00 to 20.00 percent single section **Case Material:** Metal

Insulation Resistance At Reference Temp:

6000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

NSN 5910-00-538-1420

Paper Dielectric Fixed Capacitor - Page 2 of 2



		_
Tarmina	I Curfoss	Trootmonte
ı ermini	i Suriace	Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/1f government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0