

View Online at https://aerobasegroup.com/nsn/5910-00-540-5763

# **Body Style:**

W/o mtg facilities terminal (s) on one surface

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.000 inches

# **Body Length:**

0.160 inches

#### **Body Width:**

0.160 inches

### **Body Height:**

### 0.080 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.107 inches

### **Terminal Diameter:**

Between 0.015 inches and 0.020 inches

# Schematic Diagram Designator:

No common or grounded electrode (s)

# **Capacitance Value Per Section:**

2.700 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

### **Tolerance Range Per Section:**

-0.50/+0.50 picofarads single section

### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1500

# **Test Data Document:**

06481-902059 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

# Shelf Life:



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0