

View Online at <https://aerobasegroup.com/nsn/5910-00-542-7337>

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.750 inches

Body Length:

1.312 inches

Body Width:

0.625 inches

Body Height:

2.000 inches

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Internal Electrical Connection Type:

Inserted tab

Section Quantity:

2

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

50000.000 picofarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc all sections

Tolerance Range Per Section:

-10.00 to 20.00 percent all sections

Case Material:

Metal

Insulation Resistance At Reference Temp:

6000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-c-25/15c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0