## NSN 5910-00-542-7400

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-542-7400

| Body Style:   |
|---|
| W/o mtg facilities, axial terminals   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 1.250 inches  |
| Body Diameter:  |
| 0.281 inches  |
| Body Length:  |
| 0.875 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Anode Type:   |
| Plain foil  |
| Electrical Polarization:  |
| Nonpolarized  |
| Features Provided:  |
| Hermetically sealed case  |
| Capacitance Value Per Section:  |
| 20.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 85.0 degrees celsius  |
| Dc Leakage At Maximum Operating Temp:   |
| 15.0 milliamperes   |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 25.0 dc single section  |
| Tolerance Range Per Section:  |
| -15.00/+75.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Tantalum  |
| Power Factor At Reference Tempurature In Percent:   |
| 15.0000   |
| Dc Leakage At Reference Temp:   |
| 2.500 microamperes  |
| Case Insulation Material:   |
| Plastic   |
| Test Data Document:   |
| 13499-184-723300rev11 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer |
| drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)        |

2 uninsulated wire lead

**Terminal Type And Quantity:** 

## NSN 5910-00-542-7400

Electrolytic Fixed Capacitor - Page 2 of 2



| _  |    |    |     |      |  |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: |  |
| J. | 16 |    |     | HE.  |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0