

View Online at <https://aerobasegroup.com/nsn/5910-00-543-9453>

**Body Style:**

W/thd bushing mtg, terminal (s) on one end

**Reliability Indicator:**

Not established

**Body Diameter:**

1.375 inches

**Body Length:**

3.750 inches

**Schematic Diagram Designator:**

One terminal common to each section

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

733.0

**Electrical Polarization:**

Polarized

**Mounting Facility Screw Thread Series Designator:**

Un

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Section Quantity:**

2

**Features Provided:**

Mounting hardware

**Capacitance Value Per Section:**

30.000 microfarads 2nd section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 65.0 degrees celsius

**Thread Size:**

0.875 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

450.0 dc 2nd section

**Tolerance Range Per Section:**

-10.00/+50.00 percent 2nd section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

17.0000

**Dc Leakage At Reference Temp:**

174.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0