Mica Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-543-9730

## Body Style:

Button type, w/thd mtg hole/stud

## **Reliability Indicator:**

Not established

#### Body Diameter:

0.450 inches

#### Body Length:

0.380 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## Mounting Facility Type And Quantity:

1 threaded mounting holes

#### **Capacitance Value Per Section:**

24.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

## **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

#### Case Material:

Metal

## **Quality Factor At Reference Temp:**

400.0000

## **Terminal Surface Treatment:**

Silver

## Test Data Document:

81349-mil-c-10950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

- 2 tab, solder lug Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:
- A010b0