## NSN 5910-00-547-2952

Paper Dielectric Fixed Capacitor - Page 1 of 2



- apor Brotomo i mod odpatno. I ago i or E
View Online at https://aerobasegroup.com/nsn/5910-00-547-2952
Body Style:
W/thd mtg hol (s)/stud(s) terminal(s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.380 inches
Body Length:
1.234 inches
Body Width:
1.234 inches
Body Height:
2.330 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.453 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Inserted tab
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Insulation Resistance At Maximum Operating Temp:
5.0 megohm-microfarads
Capacitance Value Per Section:
2.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

10000.0 megohms

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-547-2952

Paper Dielectric Fixed Capacitor - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0