

View Online at <https://aerobasegroup.com/nsn/5910-00-547-3029>

Thread Class:

2a

Body Style:

Plate-meshing

Overall Length:

Between 1.203 inches and 1.296 inches

Terminal Length:

0.250 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.750 inches

Overall Width:

0.620 inches

Shaft Diameter:

0.185 inches single shaft and 0.191 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.500 inches single shaft

Body Length:

Between 0.041 inches and 0.734 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Fragility Factor:

Moderately rugged

Terminal Width:

0.064 inches

Terminal Thickness:

0.016 inches

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Uninclosed

Plate Quantity:

5

Tuning Characteristic:

Straight line capacity single section

Adjustment Device Rotation:

180.0 degrees clockwise and 180.0 degrees counterclockwise

Adjustment Device Torque:

Between 1.250 inch-ounces and 6.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000.0 megohms

Plate Air Gap:

0.013 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 175.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+1.9/+4.5 single section

Nonderated Voltage Rating And Type:

500.0 ac dielectric withstanding single section

Adjustment Device Drive Type And Quantity:

1 shaft

Material:

Steatite base

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0